


DKC...H100N Cable Ladder

Overview:

Application
Cable routing

Material
Steel, strip-galv. acc. to the Sendzimir method to PN-EN 10346:2011 (SG)

Available to order:
F- steel, hot-dip galv. to PN-EN ISO 1461:2011 (HDG)
E- stainless steel sections to 3m long (SS)
L- powder coating in a full range of colours (PC)



NOTE: Cable ladder with rungs adapted for use with Cable Clamps UKZ

Available upon special order:
- cable ladders 2m long
- cable ladders 150, 250mm wide.

Versions:

Sheet thickness: 2,0 mm

Symbol	Length L [m]	Width a [mm]	Catalogue number	Quantity in box	Weight [1m]	Effective section
DKC100H100/3N	3000	100	498710	2	4,50	8200
DKC100H100/6N	6000	100	498810	2	4,50	8200
DKC200H100/3N	3000	200	498720	2	4,86	16400
DKC200H100/6N	6000	200	498820	2	4,86	16400
DKC300H100/3N	3000	300	498730	2	5,24	24600
DKC300H100/6N	6000	300	498830	2	5,24	24600
DKC400H100/3N	3000	400	498740	2	5,78	32800
DKC400H100/6N	6000	400	498840	2	5,78	32800
DKC500H100/3N	3000	500	498750	2	5,96	41000
DKC500H100/6N	6000	500	498850	2	5,96	41000
DKC600H100/3N	3000	600	498760	2	6,32	49200
DKC600H100/6N	6000	600	498860	2	6,32	49200

Connected products:



NO100N
Protective Cap
(Set)



LDCH100N
Straight
Connector



LKDCH100N
Angle Connector



LDDCH100N
Articulated
Connector -
Attachable



LDDTH100N
Articulated
Connector -
Attachable



LGTH100N
Articulated
Connector



LDC...H100N
90° Horizontal
Bend



LDZC...H100N
90° Horizontal
Bend - External



TDC...H100N
Horizontal Tee



CZDC...H100N
Horizontal
Cross-over



LPDWC...H100N
90° Vertical
Bend - Internal



LPDZC...H100N
90° Vertical
Bend - External



LPDC...H100N
Adjustable
Vertical Bend



RDSC...H100N
Straight
Reducer



RDLC...H100N
Left Reducer



RDPC...H100N
Right Reducer



UKZ1/UKZO1...
Cable Clamp