


DUC...H100N Cable Ladder

Overview:

Application
Cable routing

Material
Steel, strip-galv. acc. to the Sendzimir method to PN-EN 10346:2011 (SG)

Available to order:
F- steel, hot-dip galv. to PN-EN ISO 1461:2011 (HDG)
E- stainless steel sections to 3m long (SS)
L- powder coating in a full range of colours (PC)



NOTE: Cable ladder with rungs adapted for use with Cable Clamps UK

Available upon special order:
- cable ladders 2m long
- cable ladders 150, 250mm wide
- production capability of perforated rungs

Versions:

Sheet thickness: **2,0 mm**

Symbol	Length L [m]	Width a [mm]	Catalogue number	Quantity in box	Weight [1m]	Effective section
DUC100H100/3N	3000	100	499310	2	4,50	8200
DUC100H100/6N	6000	100	499410	2	4,50	8200
DUC200H100/3N	3000	200	499320	2	4,86	16400
DUC200H100/6N	6000	200	499420	2	4,86	16400
DUC300H100/3N	3000	300	499330	2	5,24	24600
DUC300H100/6N	6000	300	499430	2	5,24	24600
DUC400H100/3N	3000	400	499340	2	5,78	32800
DUC400H100/6N	6000	400	499440	2	5,78	32800
DUC500H100/3N	3000	500	499350	2	5,96	41000
DUC500H100/6N	6000	500	499450	2	5,96	41000
DUC600H100/3N	3000	600	499360	2	6,32	49200
DUC600H100/6N	6000	600	499460	2	6,32	49200

Connected products:



LKDCH100N Angle Connector



LDDCH100N Articulated Connector - Attachable



LGTH100N Articulated Connector



LDC...H100N 90° Horizontal Bend