

KKNd 90° Horizontal Bend 2 Comp.

Overview:

Application

Diversion in cable routing


Material

Steel, strip-galv. acc. to the Sendzimir method to PN-EN 10346:2011 (SG)

Available to order:

F- steel, hot-dip galv. to PN-EN ISO 1461:2011 (HDG)

E- stainless steel (SS)




Versions:


Sheet thickness: **1,0 mm**

Symbol	Width a [mm]	Catalogue number	Quantity in box	Weight 1 pc.
KKNd175H28	175	520817	4	0,85
KKNd190H28	190	520819	4	0,96
KKNd240H28	240	520824	4	1,22
KKNd340H28	340	520834	4	1,94


Connected products:



KN Underfloor Trunking



KNd Underfloor Trunking 2 Comp.




KNT Underfloor Trunking 3 Comp.



KKN 90° Horizontal Bend



KKNt 90° Horizontal Bend 3 Comp.




KKNM 45° Horizontal Bend



KKNMd 45° Horizontal Bend 2 Comp.



KKNMt 45° Horizontal Bend 3 Comp.



TKN Horizontal Tee



CZKN Horizontal Cross-over



LK Vertical Bend



LKd Vertical Bend 2 Comp.



LKt Vertical Bend 3 Comp.



RKN Straight Reducer



RKNd Straight Reducer 2 Comp.



RKNMt Straight Reducer 3 Comp.