

KKNt 90° Horizontal Bend 3 Comp.

Overview:

Application

Diversion in cable routing



Material

Steel, strip-galv. acc. to the Sendzimir method to PN-EN 10346:2011 (SG)

Available to order:

F- steel, hot-dip galv. to PN-EN ISO 1461:2011 (HDG)

E- stainless steel (SS)



Versions:

Sheet thickness: **1,0 mm**

Symbol	Width a [mm]	Catalogue number	Quantity in box	Weight 1 pc.
KKNt175H38	175	530917	4	1,09
KKNt190H38	190	530919	4	1,20
KKNt240H38	240	530924	4	1,48
KKNt340H38	340	530934	4	2,26

Connected products:



LKt Vertical Bend 3 Comp.




RKN Straight Reducer




RKNd Straight Reducer 2 Comp.




RKNt Straight Reducer 3 Comp.



KN Underfloor Trunking



KNd Underfloor Trunking 2 Comp.



KNT Underfloor Trunking 3 Comp.



KKN 90° Horizontal Bend



KKNd 90° Horizontal Bend 2 Comp.



KKNM 45° Horizontal Bend



KKNMd 45° Horizontal Bend 2 Comp.



KKNMt 45° Horizontal Bend 3 Comp.



TKN Horizontal Tee



CZKN Horizontal Cross-over



LK Vertical Bend



LKd Vertical Bend 2 Comp.