

KKNMt 45° Horizontal Bend 3 Comp.

Overview:

Application

Diversion in cable routing



Material

Steel, strip-galv. acc. to the Sendzimir method to PN-EN 10346:2011 (SG)

Available to order:

F- steel, hot-dip galv. to PN-EN ISO 1461:2011 (HDG)

E- stainless steel (SS)



Versions:

Sheet thickness: **1,0 mm**

Symbol	Width a [mm]	Catalogue number	Quantity in box	Weight 1 pc.
KKNMt175H38	175	531217	4	0,77
KKNMt190H38	190	531219	4	0,85
KKNMt240H38	240	531224	4	1,06
KKNMt340H38	340	531234	4	1,63

Connected products:



LKt Vertical
Bend 3 Comp.




RKN Straight
Reducer




RKNd Straight
Reducer 2
Comp.




RKNt Straight
Reducer 3
Comp.



KN Underfloor
Trunking



KNd Underfloor
Trunking 2
Comp.



KNT Underfloor
Trunking 3
Comp.



KKN 90°
Horizontal Bend



KKNd 90°
Horizontal Bend
2 Comp.



KKNt 90°
Horizontal Bend
3 Comp.



KKNM 45°
Horizontal Bend



KKNMd 45°
Horizontal Bend
2 Comp.



TKN Horizontal
Tee



CZKN Horizontal
Cross-over



LK Vertical Bend



LKd Vertical
Bend 2 Comp.