

KKNd 90° Horizontal Bend 2 Comp.

Overview:


Application

Diversion in cable routing

Material

Steel, strip-galv. acc. to the Sendzimir method to PN-EN 10346:2011 (SG)

Available to order:
F- steel, hot-dip galv. to PN-EN ISO 1461:2011 (HDG)


E- stainless steel (SS)


Versions:

 Sheet thickness: **1,0 mm**

Symbol	Width a [mm]	Catalogue number	Quantity in box	Weight 1 pc.
KKNd 175H48	175	570817	4	1,09
KKNd 190H48	190	570819	4	1,20
KKNd 240H48	240	570824	4	1,48
KKNd 340H48	340	570834	4	2,26

Connected products:



KN Underfloor Trunking




KNd Underfloor Trunking 2 Comp.




KNt Underfloor Trunking 3 Comp.



KKN 90° Horizontal Bend




KKNt 90° Horizontal Bend 3 Comp.



KKNM 45° Horizontal Bend



KKNMd 45° Horizontal Bend 2 Comp.



KKNMt 45° Horizontal Bend 3 Comp.



TKN Horizontal Tee



CZKN Horizontal Cross-over



LK Vertical Bend



LKd Vertical Bend 2 Comp.



LKt Vertical Bend 3 Comp.



RKN Straight Reducer



RKNd Straight Reducer 2 Comp.



RKNt Straight Reducer 3 Comp.