


## CWD40H22... Support Channel

### Overview:

#### Application

Used for suspending lighting, and as construction element for installing cable trays, and ladders. Used as an element for supporting Brackets WW, WWS, WS, WSZ, WZS, WWC, WWCN, WMC, WMCN, WPL, WWD, and WPT.



#### Material

Steel, strip-galv. acc. to the Sendzimir method to PN-EN 10346:2011 (SG)

#### Available to order:

**F**- steel, hot-dip galv. to PN-EN ISO 1461:2011 (HDG)

**E**- stainless steel sections to 3m long (SS)

**L**- powder coating in a full range of colours (PC)

**Important! In case of large quantity orders available for any sections up to 6m long and for channel made of steel sheet 2.5mm thick. For the assembly of support channel in combination with channel connector - use Screw Sets SGK M10x20 or SG M10x20.**

### Versions:

Sheet thickness: **1,2 mm**

| Symbol     | Length L [m] | Width a [mm] | Catalogue number | Quantity in box | Height H [mm] | Weight 1 pc. |
|------------|--------------|--------------|------------------|-----------------|---------------|--------------|
| CWD40H22/2 | 2000         | 40           | 610120           | 8               | 22            | 1,60         |
| CWD40H22/3 | 3000         | 40           | 610130           | 8               | 22            | 2,40         |
| CWD40H22/6 | 6000         | 40           | 610160           | 8               | 22            | 4,80         |

### Connected products:

