

CD28H12... Channel

Overview:

Application

Used for suspending lighting, and as construction element for installing cable trays, and ladders. Used as an element for supporting Brackets WW, WWS.

Material

Steel, strip-galv. acc. to the Sendzimir method to PN-EN 10346:2011 (SG)



Available to order:

F- steel, hot-dip galv. to PN-EN ISO 1461:2011 (HDG)

E- stainless steel sections to 3m long (SS)

L- powder coating in a full range of colours (PC)

Important! In case of large quantity orders available are any sections to 3m long.



Versions:

Sheet thickness: **1,2 mm**

Symbol	Length L [m]	Width a [mm]	Catalogue number	Quantity in box	Height H [mm]	Weight 1 pc.
CD28H12/2	2000	28	611320	20	12	0,84
CD28H12/3	3000	28	611330	20	12	1,26

Connected products:



CWZJ30H20...
Support Channel



PCWZJ... Cover
For Channel



PTJ... Perforated
Steel Band



PZC... Assembly
Plate



NO40x20
Protective Cap



NO40x47
Protective Cap



NOK...
Protective Cap



NO80x37
Protective Cap



SZB35H7... DIN
Rail



SZB35H15... DIN
Rail



TSO...
Galvanised Steel
Tape



DSO...
Galvanised Steel
Wire



SZP35H7... DIN
Rail



SZP35H15... DIN
Rail



LCW20H10
Channel
Connector



NO30x30
Protective Cap



NO40x40N
Protective Cap



NO40x60
Protective Cap



DPH... I-Beam



NO40x30
Protective Cap



NO50x30
Protective Cap