KTP35H35... Angle Profile

Overview:

Application

Supporting installation accessories of electrical rack/sub-rack cabinets, enclosures, and cases both: in systems and stand-alone, and plug-in units

Material

Steel, strip-galv. acc. to the Sendzimir method to PN-EN 10346:2011 (SG)

Available to order:

F- steel, hot-dip galv. to PN-EN ISO 1461:2011 (HDG)

E- stainless steel (SS)

L- powder coating in a full range of colours (PC)

Important! In case of large quantity orders available are any sections to 3m long.

Versions:

Sheet thickness: 1,5 mm

Symbol	Length L [m]	Width a [mm]	Catalogue	Quantity in box	Height H [mm]	Weight 1 pc.
			number			
KTP35H35/2	2000	35	620520	10	35	1,30
KTP35H35/3	3000	35	620530	10	35	1.95
K1F331133/3	3000	33	020330	1 -0	33	1,95

Connected products:

















CWZP30H20... CWZP40H22... CWZP40H47... PLP... Perfo Support ChannelSupport Channel Steel Strip

PLP... Perforated PTP20...

Band

PTP20... PZC... Assembly NO40x20 Perforated Steel Plate Protective Protective Cap

CWP40H35... Support Channel



LCW40H35 Channel Connector



LCW40H47 Channel Connector



LCM50H30 Channel Connector



NO40x47 Protective Cap



CP28H12... Channel



CP40H20... Channel



CMP40H22... LC40H20 Support Channel Channel Connector



Angle Profile









NO80x37 Protective Cap



CWP30H30 Support Channel Channel



LCW30H30 Channel Connector



LCM40H40 Connector



TSO..



Galvanised Steel_{DSO.}. Tape Galvanised Steel Wire























NO30x30

NO40x40N

NO40x60 Protective Cap Protective Cap Protective Cap

DPH... I-Beam

NO40x30 Protective Cap

NO50x30 Protective Cap

LCM40H60 Channel Connector

LCM50H50 Channel Connector

© 2024 STRADER 1/1