


BR.../1 Spacer

Overview:

Application

Application
Used as spacer protecting against crushing steel profile during installation.

Used with channel and Z-Profile .

[illegible]

Material

Steel, strip-galv. acc. to the Sendzimir method to PN-EN

10346:2011 (SG)

Available to order:

F- steel, hot-dip galv. to PN-EN ISO 1461:2011 (HDG)

E- stainless steel (SS)

L - powder coating in a full range of colours (PC)

**WE RECOMMEND USING
SPACERS BR... WHEN
SCREWING UP HEAD PLATES
WITH STEEL PROFILES.
SPACER BR...
PROTECTS AGAINST
CRUSHING CHANNEL OR Z - PROFILES
DURING INSTALLATION.**

Versions:

Symbol	Width a [mm]	Catalogue number	Quantity in box	Application	Vhodné pre
BR33/1	33	704011	50	CWT40H40, CWT40H60, CWT40H80, CMT40H60, CMT40H80	
BR34/1	34	704141	50	CMT41H41	
BR35/1	35	704131	50	CWC40H40, CMM41H41, CMPM41H82, CMMC40H40, CMC40H60	WPCW/WPCO...
BR36/1	36	704121	50	CMC41H41, CWP40H40, CMPC41H82, CMMP40H40, CMP40H60	
BR37/1	37	704111	50	CMP41H41	
BR45/1	45	704145	50	CC50H35	WPCB...
BR48/1	48	705521	50	CT55H50	WPCT...
BR50/1	50	705511	50	CC55H50	
BR51/1	51	705911	50	CE60H40	WPSE...
BR53/1	53	706021	50	CT60H40	WPST...
BR61/1	61	707021	50	CE70H50	WPCE/WPCEO...
BR63/1	63	707011	50	CT70H50	