


DGOP...H60N Cable Ladder

Overview:

APPLICATION
Cable routing

MATERIAL
Steel, strip-galv. acc. to the
Sendzimir method PN-EN 10346:2011
Available finishes:
L- powder coating in a full range of colours (PC)



- For assembly use 2 pcs of Straight connectors
LDC/LDOCH60
and 8 sets of screw SGK8x14
- For vertical direction change use 2 pcs of Articulated
Connector
LGC/LGOCH60 and 8 sets of screw SGK8x14
- For horizontal direction change use 2 pcs of Angle
Connector
LKD/LKDOCH60 and 8 sets of screw SGK8x14

Max. safe load: 20 kg/m
Max. spacing of supports: 1.5m

Versions:

Sheet thickness: 1,5 mm

Symbol	Length L [m]	Width a [mm]	Catalogue number	Quantity in box	Weight [1m]
DGOP100H60/3N	3000	100	863013	2	2,67
DGOP100H60/6N	6000	100	863010	2	2,67
DGOP200H60/3N	3000	200	863023	2	3,39
DGOP200H60/6N	6000	200	863020	2	3,39
DGOP300H60/3N	3000	300	863033	2	3,72
DGOP300H60/6N	6000	300	863030	2	3,72
DGOP400H60/3N	3000	400	863043	2	4,38
DGOP400H60/6N	6000	400	863040	2	4,38
DGOP500H60/3N	3000	500	863053	2	4,51
DGOP500H60/6N	6000	500	863050	2	4,51
DGOP600H60/3N	3000	600	863063	2	4,99
DGOP600H60/6N	6000	600	863060	2	4,99

Connected products:



LDP/LDOP...H60
90° Horizontal
Bend



LDOPE 90°
ladder bend



TDP/TDOP...H60
Horizontal Tee



CZDP/CZDOP...
60 Horizontal
Cross-over



HCZDP/CZDOPE
Horizontal
Cross-over



LPDWOP...H60N
90° Vertical
Bend - Internal



LPDZOPN 90°
Vertical Bend -
External



LDC/LDOCH60
Straight
Connector



LDOCH60E
Ladder coupler



LGC/LGOCH60
Articulated
Connector



LKD/LKDOCH60N
Angle Connector



LKD/LKDOCH60E
Angle Connector



ZM/ZMO Hold
Down Clamp



ZMOE Hold
Down Clamp



RO1... Cable
Protection Piece



UKO1E Cable
Clamp



SGN Screw Set



SM... Screw Set



NS... Nut



PP... Washer



PW... Washer