


## KBL...H110 Cable Tray

### Overview:

**Application**  
 Cable routing

**Material**  
 Steel, strip-galv. acc. to the Sendzimir method to PN-EN 10346:2011 (SG)

**Available to order:**  
 E- stainless steel (SS)  
 L- powder coating in a full range of colours (PC)



**Important!**  
 Possibility of joining cable tray KBR..., KBL..., KBJ... and KBD... sections together through sliding one into another and connector-free assembly. Cable Tray sections of KBP... can be joined up only through the use of connectors (lack of cut in the flange at the end of side profile).  
 Available when ordering in large quantity are 6m long tray sections.  
 To install cable tray use Screw Sets SGK M6x12 or SG M6x12.

### Versions:

Sheet thickness: **0,7 mm**

Symbol	Length L [m]	Width a [mm]	Catalogue number	Quantity in box	Weight [1m]	Effective section
KBL100H110/3	3000	100	121410	4	2,03	10800
KBL200H110/3	3000	200	121420	4	2,63	21800
KBL300H110/3	3000	300	121430	2	3,23	32800
KBL400H110/3	3000	400	121440	2	3,83	43800
KBL500H110/3	3000	500	121450	2	4,43	54800
KBL600H110/3	3000	600	121460	2	5,03	65800