

KSC...H200 Cable Tray

Overview:

Application

Cable routing in halls or on-site with limited number of supporting structures. High tray durability allows for applying spacing of supports even every 6m.



Material

Steel, strip-galv. acc. to the Sendzimir method to PN-EN 10346:2011 (SG)

Available to order:

F- steel, hot-dip galv. to PN-EN ISO 1461:2011 (HDG)
E- stainless steel (SS)
L- powder coating in a full range of colours (PC)

IMPORTANT! In case of large orders

- cable tray with perforated side profile
- cable tray from 2 up to 12m long
- cable tray: 1,2 and 2,5mm thick sheet.

Cable Tray adapted for installation of Cable Clamps: UKZ1, UKZ2

Versions:

Sheet thickness: **2,0 mm**

Symbol	Length L [m]	Width a [mm]	Catalogue number	Quantity in box	Weight [1m]	Effective section
KSC200H200/3	3000	200	290120	2	11,80	37800
KSC200H200/6	6000	200	290121	2	11,80	37800
KSC300H200/3	3000	300	290130	2	12,80	57800
KSC300H200/6	6000	300	290131	2	12,80	57800
KSC400H200/3	3000	400	290140	2	13,80	77800
KSC400H200/6	6000	400	290141	2	13,80	77800
KSC500H200/3	3000	500	290150	2	14,80	97800
KSC500H200/6	6000	500	290151	2	14,80	97800
KSC600H200/3	3000	600	290160	2	15,80	117800
KSC600H200/6	6000	600	290161	2	15,80	117800