


## KST...H200 Cable Tray

### Overview:

- Application**  
 Cable routing in halls or on-site with limited number of supporting structures. High tray durability allows for applying spacing of supports even every 6m.

**Material**  
 Steel, strip-galv. acc. to the Sendzimir method to PN-EN 10346:2011 (SG)

**Available to order:**  
**F**- steel, hot-dip galv. to PN-EN ISO 1461:2011 (HDG)  
**E**- stainless steel (SS)  
**L**- powder coating in a full range of colours (PC)



- IMPORTANT! In case of large orders**  
 - cable tray with perforated side profile  
 - cable tray from 2 up to 12m long  
 - cable tray: 1,2 and 2,5mm thick sheet.  
 Cable Tray adapted for installation of Cable Clamps: UKZ1, UKZ2

### Versions:

Sheet thickness: 3,0 mm

Symbol	Length L [m]	Width a [mm]	Catalogue number	Quantity in box	Weight [1m]	Effective section
KST200H200/6	6000	200	290221	2	16,30	37800
KST300H200/6	6000	300	290231	2	17,30	57800
KST400H200/6	6000	400	290241	2	18,30	77800
KST500H200/6	6000	500	290251	2	19,30	97800
KST600H200/6	6000	600	290261	2	20,30	117800