

DDMC...H55 Vertical Cable Ladder

Overview:

Application

Routing cable runs of various types in the vertical plane.

Material

Steel, strip-galv. acc. to the Sendzimir method to PN-EN 10346:2011 (SG)

Available to order:

F- steel, hot-dip galv. to PN-EN ISO 1461:2011 (HDG)


E- stainless steel to 3m lengths (SS)

L- powder coating in a full range of colours (PC)

Note:

Rungs of cable ladders installed on both sides.

Alternative cable installation in Cable Clamps UK... on both sides of the ladder.



Versions:

Sheet thickness: **2,0 mm**

Symbol	Length L [m]	Width a [mm]	Catalogue number	Quantity in box	Weight [1m]
DDMC200H55/3	3000	200	403320	1	5,08
DDMC200H55/6	6000	200	403420	1	5,08
DDMC300H55/3	3000	300	403330	1	5,60
DDMC300H55/6	6000	300	403430	1	5,60
DDMC400H55/3	3000	400	403340	1	6,12
DDMC400H55/6	6000	400	403440	1	6,12
DDMC500H55/3	3000	500	403350	1	6,64
DDMC500H55/6	6000	500	403450	1	6,64
DDMC600H55/3	3000	600	403360	1	7,16
DDMC600H55/6	6000	600	403460	1	7,16
DDMC700H55/3	3000	700	403370	1	7,76
DDMC700H55/6	6000	700	403470	1	7,76
DDMC800H55/3	3000	800	403380	1	8,32
DDMC800H55/6	6000	800	403480	1	8,32
DDMC900H55/3	3000	900	403390	1	8,84
DDMC900H55/6	6000	900	403490	1	8,84
DDMC1000H55/3	3000	1000	403391	1	9,40
DDMC1000H55/6	6000	1000	403491	1	9,40