

KCL/KCOL...H60 Cable Tray

Overview:

Application
Cable routing

Material
Steel, strip-galv. acc. to the Sendzimir method to PN-EN 10346:2011 (SG)

Available to order:
E- stainless steel (SS)
L- powder coating in a full range of colours (PC)

Important! Possibility of joining cable tray sections together through sliding one into another and connectorfree assembly.
Available when ordering in large quantity are 2m and 6m long tray sections. To install cable tray use Screw Sets SGK M6x12 or SG M6x12.



Versions:

Sheet thickness: 0,7 mm

Symbol	Length L [m]	Width a [mm]	Catalogue number	Quantity in box	Weight [1m]	Effective section
KGL/KCL50H60/2	2000	50	160324	12	0,98	2900
KGL/KCL50H60/3	3000	50	160424	12	0,98	2900
KCL/KCOL100H60/3	3000	100	160810	6	1,18	5800
KCL/KCOL150H60/3	3000	150	160815	6	1,43	8800
KCL/KCOL200H60/3	3000	200	160820	6	1,68	11800
KCL/KCOL300H60/3	3000	300	160830	4	2,18	17800
KCL400H60/3	3000	400	160240	4	2,67	23800
KCL500H60/3	3000	500	160250	2	3,17	29800
KCL600H60/3	3000	600	160260	2	3,67	35800

Connected products:



KGL/KGOL...H60 Cable Tray



NO24x35 Cable Protection Ring



KBL...H60 Cable Tray



LPLH60 Straight Connector



LPMLH60 Straight Connector