

KFJ...H60 Cable Tray

Overview:

**Planned production start in
2nd quarter of 2014**



APPLICATIONS

Cable routing

MATERIAL

Steel, strip-galv. acc. to the Sendzimir
method to PN-EN 10346:2011 (SG).

Connection of a click system. In order to provide stable electric continuity connection 1 set of screws SGKM6x12 or SGM6x12 should be used. Information about Covers for Cable Trays and Covers for Fittings

New click connection system of cable trays

Advantages of new system:

- Fast and easy assembly
- Firm click connection
- Deep stamping around the slots in the bottom increase the strength
- dense perforation with stamping around the slots for excellent heat transfer
- designed to enable cable tray installation on supports from BAKS anywhere within the system
- slotted holes Ø11 in the cable tray bottom allow for suspension on a threaded rod

Applications of Cable Trays KF...

- In electric installation assembled on grounded steel structures
- In electrical installations with safe tension
- In hydraulic, pneumatic installations etc...

Versions:

Sheet thickness: **1,0 mm**

Symbol	Length L [m]	Width a [mm]	Catalogue number	Quantity in box	Weight [1m]	Effective section
KFJ50H60/3	3000	50	162523	4	1,25	2900
KFJ100H60/3	3000	100	162623	4	1,53	5800
KFJ150H60/3	3000	150	162723	4	1,86	8800
KFJ200H60/3	3000	200	162823	4	2,13	11800
KFJ300H60/3	3000	300	162923	4	2,96	17800
KFJ400H60/3	3000	400	163023	2	3,37	23800
KFJ500H60/3	3000	500	163123	2	4,04	29800
KFJ600H60/3	3000	600	163223	2	4,64	35800