


CMC41H41...F Support Channel

Overview:

Application

Used for suspending lighting, as part of the assembly, and as construction element for installing cable trays, ladders, and Brackets **WWT, WPT, WWC, WWCN, WPL, WTL, WW, WWS/WWSO, WWD, WMC/WMCO, WMCN**.



Material

Steel, hot-dip galv. to PN-EN ISO 1461:2011 (HDG)

Available to order:

Steel, strip-galv. acc. to the Sendzimir method to PN-EN 10346:2011 (SG)

E- stainless steel, lengths up to 3 m, addition CMC41H41, CMM41H41 i CMT41H41 (SS)
L- powder coating in a full range of colours (PC)

Important!

For the assembly of support channel in combination with support channel connector use Screw Sets SGKM10x20 or SGM10x25

Versions:

Sheet thickness: **2,0 mm**

Symbol	Length L [m]	Width a [mm]	Catalogue number	Quantity in box	Height H [mm]	Weight 1 pc.
CMC41H41/02F	200	41	621202	30	41	0,35
CMC41H41/03F	300	41	621203	30	41	0,53
CMC41H41/04F	400	41	621204	30	41	0,71
CMC41H41/05F	500	41	621205	30	41	0,89
CMC41H41/06F	600	41	621206	30	41	1,06
CMC41H41/07F	700	41	621207	30	41	1,24
CMC41H41/08F	800	41	621208	30	41	1,41
CMC41H41/09F	900	41	621209	30	41	1,60
CMC41H41/1F	1000	41	621210	8	41	1,78
CMC41H41/2F	2000	41	621222	8	41	3,56
CMC41H41/3F	3000	41	621232	8	41	5,34
CMC41H41/6F	6000	41	621262	8	41	10,68