


KBL...H100 Cable Tray

Overview:

Application
 Cable routing

Material
 Steel, strip-galv. acc. to the Sendzimir method to PN-EN 10346:2011 (SG)

Available to order:
 E- stainless steel (SS)
 L- powder coating in a full range of colours (PC)




Important!
 Possibility of joining cable tray KBR..., KBL..., KBJ... and KBD... sections together through sliding one into another and connector-free assembly. Cable Tray sections of KBP... can be joined up only through the use of connectors (lack of cut in the flange at the end of side profile). Available when ordering in large quantity are 6m long tray sections.
 To install cable tray use Screw Sets SGK M6x12 or SG M6x12.

Versions:


Sheet thickness: **0,7 mm**

Symbol	Length L [m]	Width a [mm]	Catalogue number	Quantity in box	Weight [1m]	Effective section
KBL100H100/3	3000	100	111410	4	1,92	9800
KBL200H100/3	3000	200	111420	4	2,52	19800
KBL300H100/3	3000	300	111430	2	3,12	29800
KBL400H100/3	3000	400	111440	2	3,72	39800
KBL500H100/3	3000	500	111450	2	4,32	49800
KBL600H100/3	3000	600	111460	2	4,92	59800

Connected products:



KGL...H100 Cable Tray



KCL...H100N Cable Tray



NO24x35 Cable Protection Ring



LPLH100 Straight Connector