

LCC...H50 U-Shaped Connector

Overview:

APPLICATION


Connecting elements of cable runs

Material

Hot-dip galv. steel to PN-EN ISO 1461:2011 (HDG)

Available to order:
E- stainless steel (SS)

L- powder coating in a full range of colours (PC)

For the installation use 20 sets of Screw SGF M6×12


Versions:

 Sheet thickness: **2,0 mm**

Symbol	Width a [mm]	Catalogue number	Quantity in box	Weight 1 pc.
LCC50H50	45	350505	30	0,30
LCC100H50	95	350510	30	0,57
LCC200H50	195	350520	30	0,68
LCC300H50	295	350530	10	0,91
LCC400H50	395	350540	10	1,14
LCC500H50	495	350550	10	1,36
LCC600H50	595	350560	10	1,59

Connected products:



KZP...H50 Cable Tray


 KKZP...H50 90° Horizontal Bend
 KKZMP...H50 45° Horizontal Bend


TKZP...H50 Horizontal Tee



CZKZP...H50 Horizontal Cross-over



LZZP...H50 90° Vertical Bend - External



LZZMP...H50 45° Vertical Bend - External



LZWP...H50 90° Vertical Bend - Internal



LZWMP...H50 45° Vertical Bend - Internal



TRZP...H50 Vertical Tee - Lengthwise



RKZP...H50 Straight Reducer



LZCH50 Straight Connector