

KKZMP...H50 45° Horizontal Bend

Overview:

APPLICATION

Diversion in cable routing

Material


Hot-dip galv. steel to PN-EN ISO 1461:2011 (HDG)

Available to order:

E- stainless steel (SS)

L- powder coating in a full range of colours (PC)

For joining fittings to cable tray lengths use Straight Connectors LZC...



Versions:

Sheet thickness: **1,5 mm**

Symbol	Width a [mm]	Catalogue number	Quantity in box	Weight 1 pc.
KKZMP50H50	50	350805	20	0,72
KKZMP100H50	100	350810	10	1,25
KKZMP200H50	200	350820	10	1,64
KKZMP300H50	300	350830	4	2,41
KKZMP400H50	400	350840	4	3,32
KKZMP500H50	500	350850	2	4,36
KKZMP600H50	600	350860	2	5,53

Connected products:

							
KZP...H50 Cable Tray	KZLP...H50 Cable Tray with Integral Connector	KKZP...H50 90° Horizontal Bend	TKZP...H50 Horizontal Tee	CZKZP...H50 Horizontal Cross-over	LZZP...H50 90° Vertical Bend - External	LZZMP...H50 45° Vertical Bend - External	LZWP...H50 90° Vertical Bend - Internal
							
LZWMP...H50 45° Vertical Bend - Internal	TRZP...H50 Vertical Tee - Lengthwise	RKZP...H50 Straight Reducer					