

KZWC...H100 Reinforced Cable Tray


Overview:

APPLICATIONS

Cable routing.

MATERIAL

Steel, hot-dip galv.
to PN-EN ISO 1461:2011 (HDG)
Available finishes:
E - stainless steel (SS), grade 1.4301 (AISI304)
L - powder coating in a full range of colours (PC)



Advantage:

Additional top bendings increase loading capacity and protects the cables against damage during laying
To join 2 cable tray lengths firmly use either 2 pair of Straight Connector LZCH100 or 1 pc of U-Shaped Connector LCC...H100 and 16 sets of Screw SGKFM8x14 or SGFM8x14.

Versions:

Sheet thickness: **2,0 mm**

Symbol	Length L [m]	Width a [mm]	Catalogue number	Quantity in box	Weight [1m]	Effective section
KZWC100H100/3	3000	100	315410	4	5,48	9800
KZWC200H100/3	3000	200	315420	2	7,13	19800
KZWC300H100/3	3000	300	315430	2	8,72	29800
KZWC400H100/3	3000	400	315440	2	10,42	39800
KZWC500H100/3	3000	500	315450	2	12,07	49800
KZWC600H100/3	3000	600	315460	2	13,72	59800

Connected products:

							
KZLC...H100 Cable Tray with Integral Connector	LZCH100 Straight Connector	LZGCH100 Articulated Connector	LCC...H100 U-Shaped Connector	KKZC...H100 90° Horizontal Bend	KKZMC...H100 45° Horizontal Bend	TKZC...H100 Horizontal Tee	CZKZC...H100 Horizontal Cross-over
							
LZZC...H100 90° Vertical Bend - External	LZZMC...H100 45° Vertical Bend - External	LZWC...H100 90° Vertical Bend - Internal	LZWMC...H100 45° Vertical Bend - Internal	TRZC...H100 Vertical Tee - Lengthwise	RKZC...H100 Straight Reducer		