

KZLC...H200 Cable Tray with Integral Connector


Overview:

APPLICATION
Cable routing

Material
Hot-dip galv. steel to PN-EN ISO 1461:2011 (HDG)

Available to order:
E- stainless steel (SS)
L- powder coating in a full range of colours (PC)

For the installation use 14 sets of Screw SGF M8×14.



Versions:

Sheet thickness: **2,0 mm**

Symbol	Length L [m]	Width a [mm]	Catalogue number	Quantity in box	Weight [1m]	Effective section
KZLC200H200/3	3000	200	372920	2	12,01	39800
KZLC300H200/3	3000	300	372930	2	13,14	59800
KZLC400H200/3	3000	400	372940	2	15,91	79800
KZLC500H200/3	3000	500	372950	2	17,96	99800
KZLC600H200/3	3000	600	372960	2	19,80	119800

Connected products:



KZLC...H200
Cable Tray



LZCH200
Straight
Connector



LCC...H200
U-Shaped
Connector



LZGCH200
Articulated
Connector



KKZC...H200 90° Horizontal Bend



KKZMC...H200 45° Horizontal Bend



TKZC...H200
Horizontal Tee



CZKZC...H200
Horizontal
Cross-over



LZZC...H200 90° Vertical Bend - External



LZZMC...H200 45° Vertical Bend - External



LZWC...H200 90° Vertical Bend - Internal



LZWMC...H200 45° Vertical Bend - Internal



TRZC...H200
Vertical Tee -
Lengthwise



RKZC...H200
Straight
Reducer