CWZP30H20... Support Channel

Overview:

Application

Used as construction element for installing cable trays and

Hot-dip galv. steel to PN-EN ISO 1461:2011 (HDG)

Available to order:

E-stainless steel sections to 3m long (SS) L- powder coating in a full range of colours (PC)

Connecting support channel sections through sliding them one into another without the use of any connectors.



Versions:

Sheet thickness: 1,5 mm

Symbol	Length L [m]	Width a [mm]	Catalogue	Quantity in box	Height H [mm]	Weight [1m]
			number			
CWZP30H20/2	2000	30	615120	20	20	0,96
CWZP30H20/3	3000	30	615130	20	20	0,96

Connected products:

















PZC... Assembly NO40x20

CWZP40H22... CWZP40H47... KTZP35H35... Support Channel Support Channel Angle Profile

PLZT30 Strip

PLZT30 CWZP40H22... CWZP40H47... PLP... Perforated Steel Support Channel Support Channel

PLP... Perforated PTP20...

Perforated Steel



Plate









LCW40H47 Channel Connector



LCM50H30 Channel Connector













Protective Cap

















CP40H20... Channel

LC40H20 Channel Connector



CMP40H22... CMP40H22... KTP25H25... Support Channel Angle Profile

KTP35H35...

Angle Profile Protective Cap

NO80x37 Protective Cap

CWP30H30... Support Channel



















LCW30H30 Channel Connector

LCM40H40 Channel Connector

TSO..

Galvanised Steel_{DSO...}

NO30x30 Galvanised SteelProtective Cap

NO40x40N Protective Cap

NO40x60 Protective Cap

DPH... I-Beam







NO50x30 Protective Cap Protective Cap



LCM40H60 Connector



LCM50H50 Channel Connector

© 2024 STRADER 1/1