CWZP40H47... Support Channel

Overview:

Application

Used as construction element for installing cable trays and

Hot-dip galv. steel to PN-EN ISO 1461:2011 (HDG)

Available to order:

E-stainless steel sections to 3m long (SS) L- powder coating in a full range of colours (PC)

Connecting support channel sections through sliding them one into another without the use of any connectors.



Versions:

Sheet thickness: 1,5 mm

Symbol	Length L [m]	Width a [mm]	Catalogue number	Quantity in box	Height H [mm]	Weight [1m]
CWZP40H47/2	2000	40	615420	8	47	1,42
CWZP40H47/3	3000	40	615430	8	47	1,42

Connected products:

















CWZP30H20... CWZP40H22... CWZP30H20... CWZP40H22... Support ChannelSupport Channel Angle Profile

PLZT30

PLZT30 CWZP30H20... CWZP40H22... PLP... Perforated Steel Support ChannelSupport ChannelSteel Strip

PLP... Perforated PTP20...

Perforated Steel



Plate







Strip



NO40x47







PZC... Assembly NO40x20



Protective Cap



CWP40H35... LCW40H35 Support Channel Channel

LCW40H47 Channel Connector

LCM50H30 Channel Connector

Protective Cap

CP28H12... Channel







LC40H20

















Channel Connector

CMP40H22... KTP25H25... Support Channel Angle Profile

KTP35H35... Angle Profile

Protective Cap

NO80x37 Protective Cap

CWP30H30... Support Channel



















NO40x60

Protective Cap



LCW30H30 Channel Connector

LCM40H40 Channel Connector

NO50x30



Galvanised Steel_{DSO...}

NO30x30 Galvanised SteelProtective Cap

NO40x40N Protective Cap

DPH... I-Beam



NO40x30



Protective Cap Protective Cap



LCM40H60 Connector



LCM50H50 Channel Connector

© 2024 STRADER 1/1