


DUP...H80N Cable Ladder

Overview:

Application
Cable routing

Material
Steel, strip-galv. acc. to the Sendzimir method to PN-EN 10346:2011 (SG)

Available to order:
F- steel, hot-dip galv. to PN-EN ISO 1461:2011 (HDG)
E- stainless steel sections to 3m long (SS)
L- powder coating in a full range of colours (PC)



NOTE: Cable ladder with rungs adapted for use with Cable Clamps UK

Available upon special order:

- cable ladders 2m long
- cable ladders 150, 250mm wide
- production capability of perforated rungs

Versions:

Sheet thickness: 1,5 mm

Symbol	Length L [m]	Width a [mm]	Catalogue number	Quantity in box	Weight [1m]	Effective section
DUP100H80/3N	3000	100	495710	2	2,90	6200
DUP200H80/3N	3000	200	495720	2	3,17	12400
DUP300H80/3N	3000	300	495730	2	3,45	18600
DUP400H80/3N	3000	400	495740	2	3,86	24800
DUP500H80/3N	3000	500	495750	2	3,99	31000
DUP600H80/3N	3000	600	495760	2	4,27	37200

Connected products:

							
NO80N Protective Cap (Set)	LDCH80N Straight Connector	LKDCH80N Angle Connector	LDDCH80N Articulated Connector - Attachable	LGCH80N Articulated Connector	LDP...H80N 90° Horizontal Bend	LDZP...H80N 90° Horizontal Bend - External	TDP...H80N Horizontal Tee
							
CZDP...H80N Horizontal Cross-over	LPDWP...H80N 90° Vertical Bend - Internal	LPDZP...H80N 90° Vertical Bend - External	LPDP...H80N Adjustable Vertical Bend	RDSP...H80N Straight Reducer	RDLP...H80N Left Reducer	RDPP...H80N Right Reducer	