

KNt Underfloor Trunking 3 Comp.

Overview:



Application

Routing underfloor cable runs

Material

Steel, strip-galv. acc. to the Sendzimir method to PN-EN 10346:2011 (SG)

Available to order:
F- steel, hot-dip galv. to PN-EN ISO 1461:2011 (HDG)


E- stainless steel (SS)


Versions:

 Sheet thickness: **1,0 mm**

Symbol	Length L [m]	Width a [mm]	Catalogue number	Quantity in box	Weight [1m]	Effective section
KNt 175H48/2	2000	175	540517	6	3,64	8200
KNt 175H48/3	3000	175	540617	6	3,64	8200
KNt 190H48/2	2000	190	540519	6	3,76	8920
KNt 190H48/3	3000	190	540619	6	3,76	8920
KNt 240H48/2	2000	240	540524	6	4,16	11320
KNt 240H48/3	3000	240	540624	6	4,16	11320
KNt 340H48/2	2000	340	540534	4	4,96	16120
KNt 340H48/3	3000	340	540634	4	4,96	16120

Connected products:



KN Underfloor Trunking




KNd Underfloor Trunking 2 Comp.




KKN 90° Horizontal Bend



KKNd 90° Horizontal Bend 2 Comp.




KKNt 90° Horizontal Bend 3 Comp.



KKNM 45° Horizontal Bend




KKNMd 45° Horizontal Bend 2 Comp.



KKNMt 45° Horizontal Bend 3 Comp.



TKN Horizontal Tee



CZKN Horizontal Cross-over



LK Vertical Bend



LKd Vertical Bend 2 Comp.




LKt Vertical Bend 3 Comp.



RKN Straight Reducer



RKNd Straight Reducer 2 Comp.



RKNt Straight Reducer 3 Comp.