

OPZJ...H42 Horizontal Bypass

Overview:

Application

Bypassing mechanical obstacles in cable routing

Material



Steel, strip-galv. acc. to the Sendzimir method to PN-EN 10346:2011 (SG)

Available to order:

F- steel, hot-dip galv. to PN-EN ISO 1461:2011 (HDG)

E- stainless steel (SS)

L- powder coating in a full range of colours (PC)



For installation use Screw Sets SGK M6×10 or SG M6×10 and Straight Connectors LPL or LPP. Quick and convenient installation by the use of dismantled parts. This innovative solution allows for fast and safe cable laying without the need of pulling

Versions:

Sheet thickness: **1,0 mm**

Symbol	Width a [mm]	Catalogue number	Quantity in box	Weight 1 pc.
OPZJ50H42	50	147105	2	0,50
OPZJ100H42	100	147110	2	0,77
OPZJ150H42	150	147115	2	1,03
OPZJ200H42	200	147120	2	1,29
OPZJ300H42	300	147130	2	1,83
OPZJ400H42	400	147140	2	2,10
OPZJ500H42	500	147150	2	2,52
OPZJ600H42	600	147160	2	3,02

Connected products:



KAJ...H42 Cable Tray KGL...H42 Cable Tray KGJ...H42 Cable Tray KGR...H42 Cable Tray KCJ...H42 Cable Tray KCL...H42 Cable Tray KOL...H42 Cable Tray KOJ...H42 Cable Tray



KBR...H42 Cable Tray KBL...H42 Cable Tray KBJ...H42 Cable Tray SG... Screw Set SM... Screw Set