

LPMLH42 Straight Connector

Overview:

Application

Connecting cable routes.

Material


Steel, strip-galv. acc. to the Sendzimir method to PN-EN 10346:2011 (SG)

Available to order:

F- steel, hot-dip galv. to PN-EN ISO 1461:2011 (HDG)

E- stainless steel (SS)

L- powder coating in a full range of colours (PC)



Use 4 Screw Sets SGK M6×10 or SG M6×10 to install

Connected products:



KAJ...H42 Cable Tray



KGL...H42 Cable Tray



KGJ...H42 Cable Tray



KGR...H42 Cable Tray



KCJ...H42 Cable Tray



KCL...H42 Cable Tray



KOL...H42 Cable Tray



KOJ...H42 Cable Tray



KBR...H42 Cable Tray



KBJ...H42 Cable Tray



OPZJ...H42 Horizontal Bypass



OPZBJ...H42 Horizontal Bypass



OPNJ...H42 Vertical Bypass



OPNB...H42 Vertical Bypass



LUJ...H42 90° Vertical Bend



LUBJ...H42 90° Vertical Bend



LUMJ...H42 45° Vertical Bend



LUMB...H42 45° Vertical Bend



LUPJ...H42 90° Vertical Bend



LUMPJ...H42 45° Vertical Bend



TRSJ...H42 Vertical Tee - Crosswise



TRSB...H42 Vertical Tee - Crosswise



SG... Screw Set



SM... Screw Set