

LUMNJ...H30 45° Vertical Bend

Overview:

Application

Diversions in cable routing.

Material

Steel, strip-galv. acc. to the Sendzimir method to PN-EN 10346:2011 (SG)

Available to order:
F- steel, hot-dip galv. to PN-EN ISO 1461:2011 (HDG)

E- stainless steel (SS)

L- powder coating in a full range of colours (PC)


For installation use Screw Sets SGK M6×10 or SG M6×10 and Straight Connectors LPL or LPP. Quick and convenient installation by the use of dismantled parts. This innovative solution allows for fast and safe cable laying without the need of pulling

Versions:

 Sheet thickness: **1,0 mm**

Symbol	Width a [mm]	Catalogue number	Quantity in box	Weight 1 pc.
LUMNJ50H30	50	136351	1	0,25
LUMNJ100H30	100	136352	1	0,34
LUMNJ150H30	150	136353	1	0,44
LUMNJ200H30	200	136354	1	0,53
LUMNJ300H30	300	136355	1	1,72

Connected products:



KGR...H30 Cable Tray



KGL...H30 Cable Tray



KGJ...H30 Cable Tray



KBJ...H30 Cable Tray



KBR...H30 Cable Tray



KBL...H30 Cable Tray



LPLH30 Straight Connector



LPPH30 Straight Connector



LPMH30 Straight Connector



LPMLH30 Straight Connector



SGK... Screw Set SM... Screw Set