LSS N Fast Tab- Lock Fixing Bracket

Overview:

Application

Joining system components of Wire Mesh Cable Trays. For cable tray side heights H30, H60, H110.
At side height H30:
for width 100mm use 3xUSS N
for widths 200mm and 300mm use 4xUSS N.
At height H60:
for width 60 use 2xUSS N
for width 100 use 3xUSS N
for widths: 200 - 400 use 4xUSS N
for widths: 500 - 600mm use
2 X USSW + 3xUSS N.
At height H110:
for widths: 200 - 400mm use:
2 x USSW + 2xUSS N
for widths: 500 - 600mm use:
2 x USSW + 3xUSS N



Joining Wire Mesh Cable Tray Lengths

at the tray bottom. Used in a set with Fast

Tab-Lock Coupler for Wire Mesh Cable Tray

LZS with cable trays H60, H110

and widths 200 - 600mm

Connected products:

UKZ1/UKZO1... Cable Clamp

UKZ2... Cable Clamp

USSW Splice Washer Kit

USSPW/USSPWO Joint Connector

PLC23/01 Connection Piece

ZSW Center Hanger

ZS/ZSO Clamping Piece

ZPNH80... Cover Clamp

NKS Bolt Cutter

BMS Mounting Plate

BSM Side Holder

WWSS... Bracket

WFLS... Bracket

WFCS... C-Bracket

SGKM6x... Screw Set

UUS Grounding Clamp

PMC/PMCO... Snap-in Support

WSD... Ceiling Bracket

© 2024 STRADER