

KSC...H100N Cable Tray

Overview:

Application

Cable routing in halls or on-site with limited number of supporting structures. High tray durability allows for applying spacing of supports even every 6m.

Material

Steel, strip-galv. acc. to the Sendzimir method to PN-EN 10346:2011 (SG)

Available to order:

F- steel, hot-dip galv. to PN-EN ISO 1461:2011 (HDG)

E- stainless steel (SS)

L- powder coating in a full range of colours (PC)



IMPORTANT! In case of large orders

- cable tray with perforated side profile

- cable tray from 2 up to 12m long

- cable tray: 1,2 and 2,5mm thick sheet.

Cable Tray adapted for installation of Cable Clamps: UKZ1, UKZ2

Versions:

Sheet thickness: **2,0 mm**

Symbol	Length L [m]	Width a [mm]	Catalogue number	Quantity in box	Weight [1m]	Effective section
KSC200H100/6N	6000	200	220121	2	7,24	19800
KSC300H100/6N	6000	300	220131	2	8,14	29800
KSC400H100/6N	6000	400	220141	2	9,04	39800
KSC500H100/6N	6000	500	220151	2	9,94	49800
KSC200H100/3N	3000	600	220160	2	10,84	59800
KSC600H100/6N	6000	600	220161	2	10,84	59800