


KSP Cable Tray

Overview:

Application

Cable routing in halls or on-site with limited number of supporting structures. High tray durability allows for applying spacing of supports even every 6m.



Material

Steel, strip-galv. acc. to the Sendzimir method to PN-EN 10346:2011 (SG)

Available to order:

F- steel, hot-dip galv. to PN-EN ISO 1461:2011 (HDG)
E- stainless steel (SS)
L- powder coating in a full range of colours (PC)

IMPORTANT! In case of large orders

- cable tray with perforated side profile
- cable tray from 2 up to 12m long
- cable tray: 1,2 and 2,5mm thick sheet.

Cable Tray adapted for installation of Cable Clamps: UKZ1, UKZ2

Versions:

Sheet thickness: **1,5 mm**

Symbol	Length L [m]	Width a [mm]	Catalogue number	Quantity in box	Weight [1m]	Effective section
KSP200H200/3	3000	200	290020	2	9,38	37800
KSP200H200/6	6000	200	290021	2	9,38	37800
KSP300H200/3	3000	300	290030	2	10,34	57800
KSP300H200/6	6000	300	290031	2	10,34	57800
KSP400H200/3	3000	400	290040	2	11,30	77800
KSP400H200/6	6000	400	290041	2	11,30	77800
KSP500H200/3	3000	500	290050	2	12,26	97800
KSP500H200/6	6000	500	290051	2	12,26	97800
KSP600H200/3	3000	600	290060	2	13,22	117800
KSP600H200/6	6000	600	290061	2	13,22	117800