


DGOP...H60F Cable Ladder

Overview:

APPLICATION
 Cable routing

MATERIAL
 Steel, hot-dip galvanised
 to PN-EN ISO 1461:2011 (HDG)
 Available finishes:
 L- powder coating in a full range of colours (PC)



- For assembly use 2 pcs of Straight connectors LDC/LDOCH60 and 8 sets of screw SGKM8x14
- For vertical direction change use 2 pcs of Articulated Connector LGC/LGOCH60 and 8 sets of screw SGKM8x14
- For horizontal direction change use 2 pcs of Angle Connector LKD/LKDOCH60 and 8 sets of screw SGKM8x14

Max. safe load: 20 kg/m
 Max. spacing of supports: 1.5m

Versions:

Sheet thickness: 1,5 mm

Symbol	Length L [m]	Width a [mm]	Catalogue number	Quantity in box	Weight [1m]
DGOP100H60/3F	3000	100	867610	2	2,67
DGOP100H60/6F	6000	100	867611	2	2,67
DGOP200H60/3F	3000	200	867620	2	3,39
DGOP200H60/6F	6000	200	867621	2	3,39
DGOP300H60/3F	3000	300	867630	2	3,72
DGOP300H60/6F	6000	300	867631	2	3,72
DGOP400H60/3F	3000	400	867640	2	4,38
DGOP400H60/6F	6000	400	867641	2	4,38
DGOP500H60/3F	3000	500	867650	2	4,51
DGOP500H60/6F	6000	500	867651	2	4,51
DGOP600H60/3F	3000	600	867660	2	4,99
DGOP600H60/6F	6000	600	867661	2	4,99