


DUP/DUOP...H60F Cable Ladder

Overview:

APPLICATION
 Cable routing

MATERIAL
 Steel, hot-dip galvanised
 to PN-EN ISO 1461:2011 (HDG)
 Available finishes:
 L- powder coating in a full range of colours (PC)



- For assembly use 2 pcs of Straight connectors LDC/LDOCH60 and 8 sets of screw SGKM8x14
- For vertical direction change use 2 pcs of Articulated Connector LGC/LGOCH60 and 8 sets of screw SGKM8x14
- For horizontal direction change use 2 pcs of Angle Connector LKD/LKDOCH60 and 8 sets of screw SGKM8x14

Max. safe load: 20 kg/m
 Max. spacing of supports: 1.5m

Versions:

Sheet thickness: 1,5 mm

Symbol	Length L [m]	Width a [mm]	Catalogue number	Quantity in box	Weight [1m]
DUP/DUOP100H60/3F	3000	100	867710	2	2,41
DUP/DUOP100H60/6F	6000	100	867711	2	2,41
DUP/DUOP200H60/3F	3000	200	867720	2	2,69
DUP/DUOP200H60/6F	6000	200	867721	2	2,69
DUP/DUOP300H60/3F	3000	300	867730	2	2,97
DUP/DUOP300H60/6F	6000	300	867731	2	2,97
DUP/DUOP400H60/3F	3000	400	867740	2	3,38
DUP/DUOP400H60/6F	6000	400	867741	2	3,38