

KCP...H100N Cable Tray


Overview:

Application
Cable routing

Material
Steel, strip-galv. acc. to the Sendzimir method to PN-EN 10346:2011 (SG)

Available to order:
F- steel, hot-dip galv. to PN-EN ISO 1461:2011 (HDG)
E- stainless steel (SS)
L- powder coating in a full range of colours (PC)

Important! Joining cable tray sections together only through the use of connectors (lack of cut in the flange at the end of side profile).
Available when ordering in large quantity are 2m and 6m long tray sections. To install cable tray use Screw Sets SGK M6x12 or SG M6x12.



Versions:

Sheet thickness: 1,5 mm

Symbol	Length L [m]	Width a [mm]	Catalogue number	Quantity in box	Weight [1m]	Effective section
KCP100H100/3N	3000	100	110810	4	3,28	9800
KCP100H100/6N	6000	100	110811	4	3,28	9800
KCP150H100/3N	3000	150	110815	4	3,78	14800
KCP150H100/6N	6000	150	110818	4	3,78	14800
KCP200H100/3N	3000	200	110820	2	4,28	19800
KCP200H100/6N	6000	200	110821	2	4,28	19800
KCP300H100/3N	3000	300	110830	2	5,27	29800
KCP300H100/6N	6000	300	110831	2	5,27	29800
KCP400H100/3N	3000	400	110840	2	6,27	39800
KCP400H100/6N	6000	400	110841	2	6,27	39800
KCP500H100/3N	3000	500	110850	2	7,27	49800
KCP500H100/6N	6000	500	110851	2	7,27	49800
KCP600H100/3N	3000	600	110860	2	8,27	59800
KCP600H100/6N	6000	600	110861	2	8,27	59800

Connected products:

