

KZLC...H100 Cable Tray with Integral Connector

Overview:

APPLICATION
 Cable routing

Material
 Hot-dip galv. steel to PN-EN ISO 1461:2011 (HDG)

Available to order:
E- stainless steel (SS)
L- powder coating in a full range of colours (PC)

For the installation use 10 sets of Screw SGF M8×14.



Versions:

Sheet thickness: **2,0 mm**

Symbol	Length L [m]	Width a [mm]	Catalogue number	Quantity in box	Weight [1m]	Effective section
KZLC100H100/3	3000	100	312910	4	6,17	9800
KZLC200H100/3	3000	200	312920	2	8,22	19800
KZLC300H100/3	3000	300	312930	2	10,16	29800
KZLC400H100/3	3000	400	312940	2	12,11	39800
KZLC500H100/3	3000	500	312950	2	14,06	49800
KZLC600H100/3	3000	600	312960	2	16,01	59800

Connected products:



KZWC...H100
Reinforced
Cable Tray



LCC...H100
U-Shaped
Connector



LZGCH100
Articulated
Connector



KKZC...H100 90°
Horizontal Bend



KKZMC...H100
45° Horizontal
Bend



TKZC...H100
Horizontal Tee



CZKZC...H100
Horizontal
Cross-over



LZZC...H100 90°
Vertical Bend -
External



LZZMC...H100
45° Vertical
Bend - External



LZWC...H100
90° Vertical
Bend - Internal



LZWMC...H100
45° Vertical
Bend - Internal



TRZC...H100
Vertical Tee -
Lengthwise



RKZC...H100
Straight
Reducer