

KKZC...H200 90° Horizontal Bend

Overview:

APPLICATION

Diversion in cable routing

Material


Hot-dip galv. steel to PN-EN ISO 1461:2011 (HDG)

Available to order:

E- stainless steel (SS)

L- powder coating in a full range of colours (PC)

For joining fittings to cable tray lengths use Straight Connectors LZC...



Versions:

Sheet thickness: **2,0 mm**

Symbol	Width a [mm]	Catalogue number	Quantity in box	Weight 1 pc.
KKZC200H200	200	370720	4	4,52
KKZC300H200	300	370730	4	7,17
KKZC400H200	400	370740	2	9,82
KKZC500H200	500	370750	2	12,17
KKZC600H200	600	370760	2	14,80

Connected products:



KZC...H200
Cable Tray



KZLC...H200
Cable Tray with
Integral
Connector



LZCH200
Straight
Connector



LCC...H200
U-Shaped
Connector



LZGCH200
Articulated
Connector



KKZMC...H200
45° Horizontal
Bend



TKZC...H200
Horizontal Tee



CZKZC...H200
Horizontal
Cross-over



LZZC...H200 90°
Vertical Bend -
External



LZZMC...H200
45° Vertical
Bend - External



LZW...H200
90° Vertical
Bend - Internal



LZWMC...H200
45° Vertical
Bend - Internal



TRZC...H200
Vertical Tee -
Lengthwise



RKZC...H200
Straight
Reducer