

GDA...- 4-5P/DX/SX "T" diel (63-2500A)

Informácie:

Použitie

Slúži na rozdelenie a zmenu smeru rovných trás.

- verzie pre 63 A až 2500 A
- v 4 a 5 pólovom prevedení
- spájanie dielov svorkovou spojkou
- krytie IP 50, s príslušenstvom možnosť dosiahnuť až IP 55



K	400 V				400 V			
	4P	5P	4P	5P	4P	5P	4P	5P
GDA100	63-100	63-100	63-100	63-100	63-100	63-100	63-100	63-100
GDA200	125-200	125-200	125-200	125-200	125-200	125-200	125-200	125-200
GDA1000	63-100	63-100	63-100	63-100	63-100	63-100	63-100	63-100
GDA2000	125-200	125-200	125-200	125-200	125-200	125-200	125-200	125-200

Materiál

- zbernice - hliník
- kryt hliník
- štandardé dĺžky 600/500mm

Verzie:

Symbol	Pól	El. prúd [A]
GDA100102	4P - DX	63
GDA100101	4P - SX	63
GDA200102	5P - DX	63
GDA200101	5P - SX	63
GDA100106	4P - DX	250
GDA100105	4P - SX	250
GDA200106	5P - DX	250
GDA200105	5P - SX	250
GDA100116	4P - DX	500
GDA100115	4P - SX	500
GDA200116	5P - DX	500
GDA200115	5P - SX	500
GDA116116	4P - DX	1000
GDA116115	4P - SX	1000
GDA216116	5P - DX	1000
GDA216115	5P - SX	1000
GDA120116	4P - DX	1250
GDA120115	4P - SX	1250
GDA220116	5P - DX	1250
GDA220115	5P - SX	1250
GDA120122	4P - DX	2000
GDA120120	4P - SX	2000
GDA220122	5P - DX	2000
GDA220120	5P - SX	2000