

GDA...- 4-5P/DX/SX Koleno Horizontálne (250-2500A)

Informácie:

Použitie

Slúži na zmenu smeru rovných trás.

- verzie pre 250 A až 2500 A
- v 4 a 5 pólovom prevedení
- spájanie dielov svorkovou spojkou
- krytie IP 50, s príslušenstvom možnosť dosiahnuť až IP 55

Materiál

- zbernice - hliník
- kryt hliník
- štandardé dĺžky 500mm



A	4P - 4				4P - 5			
	250	500	1000	1250	2000	2500	3000	3500
250	1000	1000	1000	1000	1000	1000	1000	1000
500	1000	1000	1000	1000	1000	1000	1000	1000
1000	1000	1000	1000	1000	1000	1000	1000	1000
1250	1000	1000	1000	1000	1000	1000	1000	1000
2000	1000	1000	1000	1000	1000	1000	1000	1000
2500	1000	1000	1000	1000	1000	1000	1000	1000
3000	1000	1000	1000	1000	1000	1000	1000	1000
3500	1000	1000	1000	1000	1000	1000	1000	1000

Verzie:

Symbol	Pól	El. prúd [A]
GDA100102	4P - DX	250
GDA100101	4P - SX	250
GDA200102	5P - DX	250
GDA200101	5P - SX	250
GDA100106	4P - DX	500
GDA100105	4P - SX	500
GDA200106	5P - DX	500
GDA200105	5P - SX	500
GDA100116	4P - DX	1000
GDA100115	4P - SX	1000
GDA200116	5P - DX	1000
GDA200115	5P - SX	1000
GDA116116	4P - DX	1250
GDA116115	4P - SX	1250
GDA216116	5P - DX	1250
GDA216115	5P - SX	1250
GDA120116	4P - DX	2000
GDA120115	4P - SX	2000
GDA220116	5P - DX	2000
GDA220115	5P - SX	2000