

## GDA...- 4-5P/DX/SX Koleno Vertikálne (250-2500A)

### Informácie:

#### Použitie

Slúži na zmenu smeru rovných trás.

- verzie pre 250 A až 2500 A
- v 4 a 5 pólovom prevedení
- spájanie dielov svorkovou spojkou
- krytie IP 50, s príslušenstvom možnosť dosiahnuť až IP 55



A	4P - DX				4P - SX			
	W	H	W	H	W	H	W	H
250	40	40	40	40	40	40	40	40
500	40	40	40	40	40	40	40	40
1000	40	40	40	40	40	40	40	40
1250	40	40	40	40	40	40	40	40
1500	40	40	40	40	40	40	40	40
2000	40	40	40	40	40	40	40	40
2500	40	40	40	40	40	40	40	40

#### Materiál

- zbernice - hliník
- kryt hliník
- štandardé dĺžky 500mm

### Verzie:

Symbol	Pól	El. prúd [A]
GDA100104	4P - DX	250
GDA100103	4P - SX	250
GDA200104	5P - DX	250
GDA200103	5P - SX	250
GDA100108	4P - DX	500
GDA100107	4P - SX	500
GDA200108	5P - DX	500
GDA200107	5P - SX	500
GDA100118	4P - DX	1000
GDA100117	4P - SX	1000
GDA200118	5P - DX	1000
GDA200117	5P - SX	1000
GDA116118	4P - DX	1250
GDA116117	4P - SX	1250
GDA216118	5P - DX	1250
GDA216117	5P - SX	1250
GDA120118	4P - DX	2000
GDA120117	4P - SX	2000
GDA220118	5P - DX	2000
GDA220117	5P - SX	2000